

Clopay Commercial Garage Door Steel Insulated Thermally Broken Models 3200, 3201 & 3203



Model 3200 -- Flush stucco embossed steel exterior with light ribbed pattern

Model 3201 -- Flush woodgrain embossed steel exterior

Model 3203 -- Raised panel woodgrain embossed steel exterior

Construction

- Sections are 2" thick.
- Superior dent resistance and greater security are provided by a full 24 gauge exterior steel skin.
- Attractive stucco embossed (Model 3200) or woodgrain elegant raised panel (Model 3203) or flush (Model 3201) steel skins are prepainted inside and out for a durable, maintenance-free finish.
- Tongue and groove section joint for exceptional strength and thermal sealing.
- Virtually maintenance free because of Clopay's three-stage rustproofing and prepainting process.

Insulation

- Insulated sandwich construction consists of exterior and interior steel skins pressure bonded to an environmentally-safe polystyrene core for greater strength and quieter operation.
- Both steel skins are separated by a continuous silicone filling to form an efficient thermal break.
- Insulating R-Value of 9.1

Colors

- **Model 3200**



White



Brown

- **Model 3201**



White



Brown



Almond

- **Model 3203**




White



Brown



Almond



Sandtone

Warranty

- 10 years against rust through.
- 10 years against delamination.
- 1 year material and workmanship.

Window Options

Model 3200

- 24" x 8"; 28" x 14" or 40" x 14" window lite of cellular PVC frame construction; glazing is 1/8" DSB, 1/8" Plexiglass or 3/4" Insulated glass.
- Full vision 1/8" DSB; 1/8" Plexiglass; 1/2" Insulated; 1/2" Tempered Insulated; 1/4" Wire glass or 1/4" Tempered.

Model 3201

- 19.5" x 12" window lite of cellular PVC frame construction (full row only); glazing is 1/8" DSB; 1/2" Insulated glass or 1/8" Plexiglass.

Model 3203

- 19.5" x 12" window lite of cellular PVC frame construction; glazing is 1/8" DSB; 1/2" Insulated glass or 1/8" Plexiglass.